



iFlex Standard

Flex is a single colour, low voltage, LED strip lighting system. It uses the latest in 3528 SMD (Surface Mounted Diode) technology mounted onto a thin, flexible PCB board. Applications include kitchens, bathrooms, wardrobes, bars, retail displays, cove and accent lighting.

Key Features:

- Use PLCC-2 3528 single color SMD LEDs
- LED dimension: 3.5x2.8x1.9mm
- LED beam angle: 120degree
- Can be cut every 3LEDs in 12V & 6LEDs 24V
- LED quantity: 60LED/meter
- LED spacing: 16.6mm
- 3M self-adhesive tape on the back
- Working voltage: 24V/12V DC
- Power consumption: 4.8w/meter
- 5 year warranty



Specifications	iFlex Standard 4.8W					
Stock Code	3528-60-24-WW	3528-60-24-NW	3528-60-24-CW	3528-60-24-R	3528-60-24-G	3528-60-24-B
Description	4.8 Watts 3000K 60LEDs per/m	4.8 Watts 4000K 60LEDs per/m	4.8 Watts 5000K 60LEDs per/m	4.8 Watts Red 60LEDs per/m	4.8 Watts Green 60LEDs per/m	4.8 Watts Blue 60LEDs per/m
Colour temp.	3000K	4000K	6000K	Red	Green	Blue
Lumens	420Lm	480Lm		160Lm	320Lm	192Lm
Power W/m	4.8W					
Dimensions	10mm Wide					
CRI	80					
LED Chip Type	3528					
Voltage	24V					
Colour Options	3000K	5000K	5000K	Red	Green	Blue
Warranty	5 Years					
List price p/m	\$15.20					

Recommended accessories:

LED Power Supplies



Diffuser channels





specialized
lighting concepts

Phone: 09 273 4105
Fax: 09 273 4104

PO Box 58-983
Botany Auckland 2163

info@specializedlightingconcepts.co.nz
www.specializedlightingconcepts.co.nz