

# IFLEX PROFESSIONAL 18W

3000k | 4000k | 6000K


2216P-300

The ultimate in high quality, reliable LED strip light, iFlex professional series features high colour rendering CRI>90 for true to life reproduction of colours.

The high quality 10mm wide copper conductor features on-board constant current IC's that regulate the flow of power to each LED module and will automatically dim the strip if the operating temperature gets to high.

## Key Specification

|                               |                     |
|-------------------------------|---------------------|
| <b>LED Density / Qty/m</b>    | 300                 |
| <b>LED Chip Type</b>          | 2216                |
| <b>Power Rating</b>           | 18W/m               |
| <b>Luminous Flux</b>          | Approx. 2000lm/m    |
| <b>Colour Rendering (CRI)</b> | >95                 |
| <b>Cutable Length</b>         | Every 50mm          |
| <b>Power Input</b>            | 24V                 |
| <b>Beaming Angle</b>          | 120 Degree          |
| <b>Dimming</b>                | Dimmable (Optional) |
| <b>Waterproof</b>             | Non-Waterproof      |
| <b>Strip Width</b>            | 12mm                |
| <b>Warranty</b>               | 5 Years Warranty    |



| Product | Colour        | CCT                                                                                 | Brightness | IP Rating |
|---------|---------------|-------------------------------------------------------------------------------------|------------|-----------|
| 3000k   | Warm White    |  | 2000lm/m   | -         |
| 4000k   | Natural White |  | 2000lm/m   | -         |
| 6000k   | Cool White    |  | 2000lm/m   | -         |

## ACCESSORIES REQUIRED

- Power Supply
- Diffuser Profile
- Joiners
- Extended Tail

